

EBS-FXS 240

24 SUBSCRIBER EXTERNAL BOARD



Main Characteristics

- 24 analog FXS channels and 24 HMP channels (when used with CTI solutions)
- DSPs for processing of audio
- Web interface for control, visualization and download of logs
- Classification of call answering (Call Analyzer)

Typical Applications

- PBX
- IP PBX
- Gateway
- IVR
- DAC

Models

- EBS-FXS 240, with 24 FXS interfaces

Overview

The EBS-FXS 240 is a compact 1U and half rack (19") module designed to meet CTI market applications that require an interface with an analog extension, and is readily apparent as an excellent option for applications like IP PBX and hybrid call center systems with VoIP channels and analog extensions.

Connection of extensions to the module is done on the EBS-FXS with a 50-channel Centronics connector and interconnection of the module with the server is done via Ethernet in a local network, isolating the power part of the extensions from the internal part of the server.

The EBS-FXS 240 maintains the standard and quality of the Khomp family of boards, performing all of the audio and signaling processing within the hardware itself, independently from the applications server.

Exclusive Resources of the EBS-FXO 240

- Network channels: 24 analog FXS channels
- VoIP channels: 24 HMP channels (when used with CTI solutions)
- Network protocols: FXS
- PBX Protocols: Transfer, second line, hold and conference.

Physical characteristics:

- Connectors: 50 channels Centronics
- Weight: 2.70Kg
- Ambient operating temperature: 0°C to 35°C
- Withstands humidity: of up to 90% without condensation
- Maximum power consumption

- Compatible with FOP (Flash Operator *Panel*)

Resources available on the entire EBS family of products

Voice processing

High capacity resources:

- All voice resources available simultaneously on all channels
- DSPs for processing of audio and signaling

Detection and generation of tones (DSP)

- MFC exchange (R2 signaling)
- Detection and generation of DTMF digits, fax tones, 425Hz (dial tone) and TDD messages (*Telecommunications Device for the Deaf*)
- Detection of intercept tones (voice mail, collect calls, etc.)
- Generation of programmable tones (beep)
- Detection of silence and presence of audio before and after answering
- Detection of fax signal and voice mail with standard signaling: 600Hz/450ms – 1000Hz/450ms or 300Hz/250ms
- Detection of programmable frequencies (for example: portability tone, non-standard voice mail, etc)

Audio enhancement features

- DTMF suppression
- Manual and automatic volume control (AGC)
- *Carrier grade* echo canceling in hardware
 - Up to 64ms (512 TAPS) simultaneously on all channels, independent of other resources
 - Convergence and automatic delay adjustment during the entire call
 - Compatible with ITU-T G.165 and G.168 norms (2000 and 2002)

Call signaling and handing

- Detection of collect calls through recognition of tones, signaling or double answering
- Call progress for generation of call control events in FXO interfaces and PBX protocols
- Classification of call answering (*Call Analyzer*)

High availability

- 2 Ethernet ports for server connection (network redundancy)
- Server redundancy (supports virtual IP)

Features programmable via API K3L

Switching of channels:

- Conference calls with up to 5 participants between any channels
- Full commutation between all channels and between modules

Recording and reproduction of voice messages

- Full-duplex mono or stereo recording
- Codecs available for recording and reproduction: G.711 (A-law and μ -law), GSM and ADPCM, PCM8, PCM16 and AMR.
- Reproduction of messages (play) in the PCM8, PCM11, PCM16, A-law and μ -law, GSM and DVI4 (ADPCM) formats

VoIP channel features

- All voice resources available for network and VoIP channels
- VoIP calls use the host Ethernet port (fast or giga ethernet)
- Codecs available for VoIP: G.711 (A-law and μ -law), ADPCM, GSM, iLBC

OAMPT

- Automated installer for updating and implementing new systems
- Web system for configuration, monitoring and diagnostics
- Native integration with SNMP
- Signaling analyzer
- Remote monitoring in real time (via web)
- Web interface for control, visualization and download of logs

Physical Characteristics

- Standard 1U Module and 1/2 19" rack
- Measurements in mm: 44.5 (height) x 220.5 (width) x 280 (length)
- Power source: Full Range (100~240Vac - 50/60 Hz)

Guarantees and Certifications

- Factory warranty 3 years
- The entire EBS line is Anatel certified
- ISO 9001:2008 Industry certified

PATCH PANEL

EXCLUSIVE ACCESSORY FOR EBS-FXS AND EBS-FXO HI

Khomp patch panels were developed to work in conjunction with the EBS-FXS 240 and EBS-FXO HI products in the conversion of Centronics-type inputs to RJ11 outputs. This way, with one patch panel it is possible to convert 1 Centronics input into 24 RJ11 ports on the 24-port model, or 2 Centronics connectors to 48 RJ11 ports, on the 48 port model.

MPE-FXS 240

EXCLUSIVE ACCESSORY FOR EBS-FXS 240

Developed exclusively for the EBS-FXS 240, the function of the MPE-FXS 240 protection module is to protect the equipment from atmospheric discharges and electrical power surges that can hit the equipment extensions. With a compact design, it is directly attached to the EBS-FXS 240, making a series of connections and cables linked to the individual units unnecessary.

Other Product Images



Rear view



Example of 7 EBS modules arranged in a standard 19" rack

Application Model

